



AMORTI CHOC

VIBRATION ABSORPTION

FABRICATION
FRANÇAISE

Ref: 0018

DESCRIPTION

Flat and absorbing insole for more everyday comfort

KEYS FEATURES

- > Absorption of shocks and vibration
- > Anti-odour

FIELD OF USE

- All work and activity sector

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- All safety shoes and boots

CHARACTERISTICS

- Material with a great absorption of shocks
- Exclusive S3F® treatment*
- Antistatic

BENEFITS

- Prevents joints and back pains
- Prevents back and foot fatigue
- Prevents the development of odours and the growth of bacteria and fungi responsible for fungal infections*.

Size

VS : 35 to 50

AG : 36/37 to 48/49

Standards

- EN 12746
- EN 13520
- 20344 §5.10



©JLF Pro



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT

DOWNLOADING

OF PRODUCT DATASHEETS AND
DOCUMENTS ON WEBSITE

www.jlf-pro.com



AMORTI CHOC - REF :0018

COMPOSITION / MATERIAL

- 100% polyamide non-woven textile coating with biocide permanent treatment
- Visco-elastic latex foam base with biocide and antistatic treatment
- *Contains biocides : zinc pyrithione

USE / CARE INSTRUCTIONS & ADVICES

- Place the textile side in contact with the foot.
- For best performance and efficiency, we recommend removing your insoles from your shoes every evening to dry them.
- Non-washable insole (treated insole)

LIFESPAN

5 to 6 months

The efficiency of the treatment may change more or less depending on criteria such as intensity of the sudoral flow, the nature of the shoe articles, the body hygiene,...

S3F® TREATMENT

- Effective on the foot on most bacteria causing unpleasant foot odour. (Staphylococcus aureus, Staphylococcus epidermidis, Corynebacterium minutissimum, brevibacterium epidermidis, Propionibacterium granulosum)
- Effective on the foot in up to 95% of cases of fungi and up to 99% of cases of nail fungi. (Trichophyton rubrum, Trichophyton mentagrophytes, Candida parapsilosis)

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Water absorption : Water desorption :	EN 12746	Absorption power : Desorption % of water after 16 hours :	94 mg/cm ² 106%
Resistance to abrasion	EN 13520	Cycles to produce a hole > Dry test > Wet test	> 25 600 > 12 800
Antistatic behaviour	20344 §5.10	> Electrical resistance after conditioning in dry atmosphere > Electrical resistance after conditioning in wet atmosphere	> Compliant > Compliant

Creation Date :
01/11/2020-V1

Revision Date :
NOT CONCERNED



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document