



LA VAGUE



©JLF Pro

Ref: 0082

FABRICATION
FRANÇAISE

DESCRIPTION

Prevents the development of odours and the growth of bacteria and fungi responsible for fungal infections*.

KEYS FEATURES

- > Exclusive S3F* treatment : anti-odour
- > Extra thin and micro perforated

FIELD OF USE

- All work and activity sector

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- All safety shoes and boots

CHARACTERISTICS

- Exclusive S3F* treatment
- Extra thin and micro perforated
- Reinforced foot ventilation
- Anti-slip

BENEFITS


- Prevents the development of odours and the growth of bacteria and fungi responsible for fungal infections*.
- Better foot ventilation

Size
from 35 to 50

Standards
· NF EN 12746
· NF EN 13520



COMPLEMENTARY PRODUCTS



0368-FRAICHEUR



0610-DESINFECTANT DESODORISANT



LA VAGUE - REF : 0082

COMPOSITION / MATERIAL

- Comfort needle punched fabric in polyester with biocide treatment*
- Under-layer : no-slip activated carbon latex foam
- *Contain biocide : Octhiline (ISO)

LIFESPAN

3 months

The efficiency of the treatment may change more or less depending on criteria such as intensity of the sudoral flow, the nature of the shoe articles, the body hygiene,...

S3F® TREATMENT

- Effective on the foot in up to 95% of cases on fungi and up to 99% of cases on nail fungi. (Trichophyton rubrum, Trichophyton mentagrophytes, Candida parapsilosis)
- Effective on the foot on most bacteria causing unpleasant foot odour. (Staphylococcus aureus, Staphylococcus epidermidis, Corynebacterium minutissimum, brevibacterium epidermidis, Propionibacterium granulosum)

USE / CARE

INSTRUCTIONS & ADVICES

- Place the green textile side in contact with the foot.
- For best performance and efficiency, we recommend removing your insoles from your shoes every evening to dry them.
- The insole is not washable (treated insole)

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Water absorption : Water desorption :	NF EN 12746	Absorption power : Desorption % of water after 16 hours :	159 mg/cm ² 101%
Resistance to abrasion	NF EN 13520	Cycles to produce a hole > dry test: > wet test:	> 51 200 > 38 400

Creation Date :
01/11/2020-V1

Revision Date :
NON CONCERNE



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document