



© JLFF Pro

SAFETY PLUS

ANATOMICAL AND ANTI-FATIGUE

Ref: 0093

DESCRIPTION

Antistatic insole, S3F® treated and shock-absorbing with foot arch support for more comfort

KEYS FEATURES

- > Shock and vibrations absorption
- > Anatomical and Anti-odour
- > PU foam made of 80% recycled materials and more breathable insole (NEW 2021)

FIELD OF USE

- All work and activity sector

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- All safety shoes and boots

CHARACTERISTICS

- The microfiber provides provides comfort and softness while being ventilated, abrasion-resistant and moisture-absorbing.
- The insert at the front of the foot supplies additional comfort around the metatarsal supports.
- PORON® technology in the heel insert distributes the pressure and significantly reduces shocks and vibration around the calcaneus (heel bone).
- Exclusive S3F® treatment*
- Antistatic

BENEFITS

- Long lasting comfort sensation thanks to the shock absorption
- Optimal protection of the joints in the lower limbs and the spinal column thanks to the heel insert
- Prevents the development of odours and the growth of bacteria and fungi responsible for fungal infections*.

Size

VS / AG : 36/37 to 48/49

Standards

- ISO 20344:2011 §7.2
- ISO 20344:2011 §6.12
- 20344 §5.10



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT



SAFETY PLUS - REF : 0093

COMPOSITION / MATERIAL

- 100% polyester microfibre top
- PU foam under-layer made of 80% recycled materials (NEW 2021)
- Perforated EVA foam front insert
- Poron® cushioned heel insert
- Conductive sewing thread made of continuous multi-filament yarn polyamide (80%) polyester-stainless steel(20%)
- *Contain biocide : Dimethyloctadecyl[3-(trimethoxysilyl)propyl]ammonium chloride

LIFESPAN

5 to 6 months

The efficiency of the treatment may change more or less depending on criteria such as intensity of the sudoral flow, the nature of the shoe articles, the body hygiene,...

USE / CARE INSTRUCTIONS & ADVICES

- Place the textile side in contact with the foot.
- For best performance and efficiency, we recommend removing your insoles from your shoes every evening to dry them.
- Non-washable insole (treated insole)

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Water absorption and desorption :	ISO 20344:2011 §7.2	Water absorption power : Water desorption :	99 mg/cm ² 100%
Resistance to abrasion	ISO 20344:2011 §6.12	Cycles to produce a hole : > Dry test > Wet test	> 25 600 > 12 800
Electrical resistance antistatic behaviour	20344 §5.10	Conditioning in dry atmosphere > left foot > right foot (tested with an antistatic shoe with a value of 20 Mohms) Conditioning in wet atmosphere > left foot > right foot (tested with an antistatic shoe with a value of 1,7 Mohms)	44,0 Mohms 44,0 Mohms 1,8 Mohms 2,3 Mohms

Creation Date :
01/11/2020-V2

Revision Date :
NOT CONCERNED



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document