



FLAT 1,20 M LACES

Ref: 0412

FABRICATION
FRANÇAISE

DESCRIPTION

Flat laces in polyester for safety shoes

KEYS FEATURES

- > Resistant to abrasion
- > Resistant to pulling
- > Resistant to breaking

FIELD OF USE

- All work and activity sector

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- Safety shoes

CHARACTERISTICS

- Length 1,20 m - width 7 mm - thickness 0,8 mm
- Compliant NF G07 002 and EN ISO 22 774 : resistant to pulling, abrasion and elongation to break

BENEFITS

- Available in differents colours

Size
1,20 m

Couleurs
Black
Brown
Grey
White

Standards
· EN ISO 22 774
· NF G 07 002
· NF G 07 002



COMPLEMENTARY PRODUCTS



0534-CHAUSSE PIED METAL



0610-DESINFECTANT DESODORISANT



FLAT 1,20 M LACES - REF : 0412

COMPOSITION / MATERIAL

- Base : 100% polyester
- Weft and binding thread: 100% polyester
- End caps: cellulose acetate

USE / CARE INSTRUCTIONS & ADVICES

- Tighten the laces from the toe, eyelet by eyelet, to adjust the shoe. Finish by tying the laces, keeping them under pressure.
- This operation should be repeated every 2 or 3 hours, especially at high or low temperatures.
- Wash at 30° C

LIFESPAN

NRT

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Resistance to abrasion	EN ISO 22 774	with a 1 kg weight	6000 cycles
Tensile strength	NF G 07 002	Tensile strength	500 N
Elongation to break	NF G 07 002	Elongation to break	18%

Creation Date :
01/12/2020-V1

Revision Date :
NOT CONCERNED



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document