



ROUND 1,50 M LACES

FABRICATION
FRANÇAISE

Ref: 0417

DESCRIPTION

Round laces in polyester for safety shoes

KEYS FEATURES

- > Resistant to abrasion
- > Resistant to pulling
- > Resistant to breaking

FIELD OF USE

- All work and activity sector

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- Safety shoes

CHARACTERISTICS

- Length 1,50 m - diameter 6 mm (+/- 0,5)
- Compliant NF G07 002 and EN 22774 : resistant to pulling, abrasion and elongation to break
- Cotton wick core for a higher resistance
- Tips in cellulose acetate

BENEFITS

- Available in differents colours : black or brown



COMPLEMENTARY PRODUCTS



0534-CHAUSSE PIED METAL



0610-DESINFECTANT DESODORISANT

Size
1,50 m

Couleurs
Black
Brown

Standards
• EN 22774
• NF G 07 002
• NF G 07 002



ROUND 1,50 M LACES - REF : 0417

COMPOSITION / MATERIAL

- Cover: 100% polyester
- Core: Cotton wick
- End caps: cellulose acetate

USE / CARE INSTRUCTIONS & ADVICES

- Tighten the laces from the toe, eyelet by eyelet, to adjust the shoe. Finish by tying the laces, keeping them under pressure.
- This operation should be repeated every 2 or 3 hours, especially at high or low temperatures.
- Wash at 30°C

LIFESPAN

NRT

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Resistance to abrasion	EN 22774	Resistance to abrasion	> 10 000 cycles
Tensile strength	NF G 07 002	Tensile strength	>800 N
Elongation to break	NF G 07 002	Elongation to break	31%

Creation Date :
01/12/2020-V1

Revision Date :
NOT CONCERNED



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document