



FIRE-RETARDANT 1,50 M LACES

FABRICATION
FRANÇAISE

Ref: 0496

DESCRIPTION

Fire-retardant 1,50m laces specially designed for fireman's safety shoes and boots.

KEYS FEATURES

- > Does not shrink in heat
- > Resistant to abrasion

FIELD OF USE

- All trades and industries, specially firemen and welding works

WORKING ENVIRONMENT

- All environment

COMPATIBILITY

- Safety shoes and fireman's boots



©JLFF Pro



CHARACTERISTICS

- Length 1,50 m - diameter 5 mm (+/- 0,5)
- Sleeve made of polyester fibers with ignifuge treatment to resist heat and small incandescent splashes
- Cotton wick core for a higher resistance
- Tips in cellulose acetate
- Compliant EN 15090\$7.3

BENEFITS

- Ignifuge treatment



COMPLEMENTARY PRODUCTS



0534-CHAUSSE PIED METAL



0610-DESINFECTANT DESODORISANT

Size
1,50 m

Couleurs
Black

Standards
· EN 15090\$7.3
· EN 22774
· NF G 07 002

JLFFPro

GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon - France
Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89

DOWNLOADING
OF PRODUCT DATASHEETS AND
DOCUMENTS ON WEBSITE
www.jlf-pro.com



FIRE-RETARDANT 1,50 M LACES - REF : 0496

COMPOSITION / MATERIAL

- Core: cotton wick
- Sheath: polyester fibres with ignifuge treatment
- End caps: cellulose acetate

USE / CARE

INSTRUCTIONS & ADVICES

- Tighten the laces from the toe, eyelet by eyelet, to adjust the shoe. Finish by tying the laces, keeping them under pressure.
- This operation should be repeated every 2 or 3 hours, especially at high or low temperatures.

LIFESPAN

NRT

SHIPPING AND STORAGE INSTRUCTIONS

- If the product is altered, it should be discarded because it may have lost its qualities.

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
Resistance to flames	EN 15090§7.3	Resistance to flames	CONFORM
Resistance to abrasion	EN 22774	Resistance to abrasion	>10 000 cycles
Resistance to pulling	NF G 07 002	Resistance to pulling	100 DaN
Elongation to break		Breaking elongation	27%

Creation Date :
01/12/2020-V1

Revision Date :
NOT CONCERNED



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document