



## TIGERA 1

### WELDING TIG WIG GLOVE



EN 388



2 1 2 1 X

EN 407



4 1 2 X 4 X

©JLF Pro

*R é f : 2102*

#### DESCRIPTION

Glove for spot welding works

#### KEYS FEATURES

- > High dexterity
- > High touch sensitivity
- > Goatskin is lightweight thin and flexible

#### FIELD OF USE

- Steel industry and metalworking : B type welding work

#### WORKING ENVIRONMENT

- Dry environment

#### CHARACTERISTICS

- Hand made of natural goathide
- Split leather cuff
- Sewn with Kevlar®
- Wing thumb

#### BENEFITS

- Glove against mechanical and thermal risks and for precision welding works like TIG/WIG.
- Ease of movement, high dexterity
- A selection of materials and Kevlar® seams for extra strength

#### Size

VR / AG : 7 to 11

#### Standards

- EN 420 + A1 (2010)
- EN 388 (2016)
- EN 407 (2004)
- EN 12477+A1(2005)



#### COMPLEMENTARY PRODUCTS



0088-CERA PLUS



0610-DESINFECTANT DESODORISANT



TIGERA 1 - REF : 2102

### COMPOSITION / MATERIAL

- Goat hide leather
- Natural split cowhide leather
- Para-aramide for seams

### LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

### REGULATION

CE marking according to EU 2016/425  
Certificate N° 0072/2697/162/06/18/0117



### USE / CARE

#### INSTRUCTIONS & ADVICES

- Protective glove against mechanical and thermal risks, fire, contact heat, convective heat, and small splash of liquid metal during handling work. Can be used for welding work such as TIG/WIG in dry environment.
- B type gloves are recommended for precision welding processes, such as TIG/WIG.
- At present, there is no standardized test method for detecting the UV penetration through the gloves' materials used. Nevertheless, the current methods to manufacture protective welding gloves do normally not allow the UV penetration.
- This glove must not be used when there is a risk of snapping up by machines in movement.
- Clean on surface with a wet rag. Dry to room temperature.
- After every use, make sure the glove does not have any ripping, large holes or soiling potentially affecting the properties and protection levels. If there is, the product must be discarded.

### SHIPPING AND STORAGE INSTRUCTIONS

- Keep in the original packaging, normal temperature and moisture, opened and ventilated room. Clean on surface with a wet rag.

### LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420 + A1 (2010)	Dexterity :	5/5
Mechanical Risks	EN 388 (2016)	Abrasion resistance: Blade cut resistance: Tear strength resistance: Puncture resistance: Cut resistance method EN ISO 13997:	2 / 4 1 / 5 2 / 4 1 / 4 X / A-F
Heat and Fire risks	EN 407 (2004)	Burning behaviour: Contact heat: Convective heat: Radiant heat: Small splashes of molten metal: Large quantities of molten metal:	4 / 4 1 / 4 2 / 4 X / 4 4 / 4 X / 4
Welding Glove	EN 12477+A1(2005)		B TYPE

Creation Date :  
01/10/2019-V1

Revision Date :  
décembre 2022



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89  
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document