



INFORMATION & USING INSTRUCTION

TIGERA 1

DESCRIPTION : Glove with hand made of goat hide and 15 cm split leather cuff.

FIELD OF USE :

This glove protects against mechanical risks, fire, contact heat, convective heat and small molten metal splashes when handling and can be used for welding works such as TIG/WIG in dry environment.

SIZES: 6 ☐ 7 ☒ 8 ☒ 9 ☒ 10 ☒ 11 ☒ 12 ☐ 13 ☐

MARKING



This item complies to the Regulation 2016/425 requirements.

It has been subjected to the EC type certificate n° 0072/2697/162/06/18/0117 issued by IFTH - (n° 0072) – Avenue Guy de Collongue – 69134 – ECULLY – CEDEX - FRANCE

STANDARDS REFERENCES

Properties according to the European standards EN 420 +A1 (2010), EN 388 (2016), EN 407 (2004) et EN 12477 (2005) :

A high level shows a good protection. (0 = level 1 not reached; X = not tested).

EN 388 (2016) : Mechanical Risks



Abrasion : 2 / 4
Cut *couptest* : 1 / 5
Tear : 2 / 4
Puncture : 1 / 4
Cut ISO : X

EN 407 (2004) : Heat and Burn



Burning behaviour : 4 / 4
Contact heat : 1 / 4
Convective heat : 2 / 4
Radiant heat : X / 4
Small splashes of molten metal : 4 / 4
Large quantities of molten metal : X / 4

EN 420 +A1 (2010) : General requirements

Dexterity : 5 / 5

EN 12477 +A1 (2005) : WELDING

TYPE B

Levels of performances are obtained with tests executed in environment conditions defined in the standards.

Thus, each use in new conditions are the concern of user's responsibility.

LIMIT OF USE :

B type gloves are recommended for spot welding works such as TIG/WIG.

At present, there is no standardised test method for detecting the U.V penetration through the gloves' materials used. Nevertheless, the current methods to manufacture protective welding gloves do normally not allow the U.V penetration. As well, arc welding settings up do not allow a welder protection in case of a direct contact with all low voltage parts.

This glove must not be used when there is a risk of snapping up by machines in movement.

CATEGORY PPE II

STORAGE & MAINTENANCE INSTRUCTIONS:

Clean on surface with a wet rag. Dry to room temperature.

Keep in the original packaging, normal temperature and moisture, opened and ventilated room.

Recycling under user's responsibility. We do not guarantee the recycled products levels of performance.

After each use check that PPE does not have any tear, hole, large burns or dirt which could lead to less protection and properties of the item. If so the glove must be thrown on scrapheap.

CE DECLARATION OF CONFORMITY is available on the following website: www.jlf-pro.com

HANDEX

4, Rue du Président Carnot – 69002 - LYON

Tel. : (33) 478370707

FRANCE