



MIGERA HYDRO

WATER REPELLENT AND BREATHABLE



EN 388



3 1 4 2 X

EN 407



4 1 3 1 4 2

©JLF Pro

Réf: 2108

DESCRIPTION

Protective glove exclusively against mechanical and thermal hazards and for welding work such as ARC welding, MIG-MAG welding and TIG-WIG.

KEYS FEATURES

- > Water repellent smooth leather for dexterity and comfort
- > Arc and MIG MAG, and/or TIG-WIG welding

FIELD OF USE

- Steel industry and metalworking : A and B types welding work

WORKING ENVIRONMENT

- Dry and/or wet environment

CHARACTERISTICS

- Water repellent grain leather
- 15 cm natural split leather cuff
- Sewn with para-aramide for extra seams strength

BENEFITS

- B and A types glove recommended for several welding works types.
- Offers a high level of dexterity and grip
- Can be used in a humid environment

Size

VR / AG : 9 to 12

Standards

- EN 420:2003+A1:2009
- EN 388:2016
- EN 407: 2004
- EN 12477+A1(2005)



COMPLEMENTARY PRODUCTS



0088-CERA PLUS



0610-DESINFECTANT DESODORISANT



MIGERA HYDRO - REF : 2108

COMPOSITION / MATERIAL

- Water repellent grain leather
- Natural split leather
- Para-aramide for seams

LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

REGULATION

CE marking according to EU 2016/425
Certificate N° 0075/2697/162/01/19/0278



USE / CARE

INSTRUCTIONS & ADVICES

- Protective glove exclusively against mechanical and thermal risks and for welding work such ARC welding, MIG-MAG welding and TIG-WIG in dry and/or wet environment.
- B and A type gloves are recommended for all welding works, even the precision welding processes.
- At present, there is no standardized test method for detecting the UV penetration through the gloves' materials used. Nevertheless, the current methods to manufacture protective welding gloves do normally not allow the UV penetration.
- As well, arc welding settings up do not allow a welder protection in case of a direct contact with all low voltage parts.
- This glove must not be used when there is a risk of snapping up by machines in movement.
- Clean on surface with a wet rag. Dry to room temperature.

SHIPPING AND STORAGE INSTRUCTIONS

- Keep in the original packaging, normal temperature and moisture, opened and ventilated room.

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420:2003+A1:2009	Dexterity : Water vapour permeability : Resistance to water penetration :	5 / 5 1 / 1 2 / 4
Mechanical Risks	EN 388:2016	Abrasion resistance: Blade cut resistance: Tear strenght resistance: Puncture resistance: Cut resistance method EN ISO 13997:	3 / 4 1 / 5 4 / 4 2 / 4 X / A-F
Heat and Fire risks	EN 407: 2004	Burning behaviour: Contact heat: Convective heat: Radiant heat: Small splashes of molten metal: Large quantities of molten metal:	4 / 4 1 / 4 3 / 4 1 / 4 4 / 4 2 / 4
Welding Glove	EN 12477+A1(2005)		TYPE A and TYPE B

Creation Date :
01/10/2019-V3

Revision Date :
décembre 2023



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document