



POLYTOUCH

MULTIPURPOSE



EN 388



4 X 4 3 D



TOUCHSCREEN

©JLFF Pro

Ref: 2301

DESCRIPTION

13 gauge knitted glove with nitrile foam coating, for all handling works where a cut protection is required

KEYS FEATURES

- > Multipurpose glove with optimal protection and dexterity
- > 2COVER™ process reinforcement
- > Suitable for touchscreen

FIELD OF USE

- Handling and/or assembly works where a cut protection is needed

CHARACTERISTICS

- 13 gauge knitted glove made of cut resistant fibers
- Black nitrile foam palm coating
- 2COVER™ process reinforcement to extend lifespan of the product by protecting this critical area
- Knitwrist for a perfect fit
- Silicone free
- EN 1149-2 standard tested

BENEFITS

- Technical fibers and nitrile coating combination for a high level of cut protection
- 2COVER™ process reinforcement to extend lifespan and a higher resistance
- Good grip, even in greasy environment
- Suitable for touchscreen : time-saver and higher security

Size
VR : 7 to 12

Standards
· EN ISO 21420:2020
· EN 388:2016+A1:2018

WORKING ENVIRONMENT

- Dry and/or greasy environment



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT



GRUPE JLFF - 4 rue du Président Carnot - 69002 Lyon - France
Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89

DOWNLOADING
OF PRODUCT DATASHEETS AND
DOCUMENTS ON WEBSITE
www.jlff-pro.com



POLYTOUCH - REF : 2301

COMPOSITION / MATERIAL

- 13 gauge knitted glove with UHMPWE, nylon, Lycra®, carbon fiber, fiberglass, polyester
- Palm and fingertips nitrile coating
- Reinforcement between thumb and forefinger with black nitrile coating
- 13 gauge knit wrist with UHMPWE, nylon, Lycra®, carbon fiber, fiberglass, polyester and elastic yarn
- Binding color per size

LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

REGLEMENTARY

CE marking according to EU 2016/425
Certificate N° 0075/4722/162/03/23/0510



USE / CARE INSTRUCTIONS & ADVICES

- Protective glove for handling of sharp-edged objects in dry and/or greasy environment
- This glove being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.
- This glove shall not be in contact with fire.

SHIPPING AND STORAGE INSTRUCTIONS

- Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C.
- Storage under excessive temperatures and for a long time (>1 month) can lead to the product deterioration.
- By nature, nitrile is sensitive to temperature changes.

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN ISO 21420:2020	Dexterity : Electrical resistance (20°C/85%RH) on Palm according to EN 1149-2(1997) : Electrical resistance (20°C/85%RH) on cuff according to EN 1149-2(1997) :	5/5 1,4 x 108Ω ≤1,00 x 105Ω
Mechanical Risks	EN 388:2016+A1:2018	Abrasion resistance: Blade cut resistance: Tear strength resistance: Puncture resistance: Cut resistance method EN ISO 13997:	4 /4 X /5 4 /4 3 /4 D /A-F

Creation Date :
01/10/2019-V1

Revision Date :
21-08-2023-V2



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document