



FITGRIP

SECOND SKIN AND EXCELLENT GRIP



©JLFF Pro

R é f : 2303

DESCRIPTION

15 gauge knitted glove with nitrile foam enduction, for precision assembly works

KEYS FEATURES

- > Second skin effect
- > Excellent grip in every condition

FIELD OF USE

- Precision works

WORKING ENVIRONMENT

- Dry and/or greasy environment

CHARACTERISTICS

- 15 gauge knitted glove, with nitrile foam palm coating
- Knitwrist for a perfect fit
- Silicone free

BENEFITS

- Second skin comfort and perfect fit
- Excellent grip in dry and/or greasy environment

Size

VR / AG : 7 to 11

Standards

- EN 420:2003+A1:2009
- EN 388:2016



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT

DOWNLOADING

OF PRODUCT DATASHEETS AND
DOCUMENTS ON WEBSITE

www.jlf-pro.com



FITGRIP - REF : 2303

COMPOSITION / MATERIAL

- 15 gauge knitted glove with texturized nylon
- Palm and fingertips black nitrile coating
- 15 gauge knit wrist with texturized nylon and elastic yarn
- Binding color per size

LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

REGULATION

CE marking according to EU 2016/425
Certificate N°0075/2697/162/03/19/0905

USE / CARE
INSTRUCTIONS & ADVICES

- Protective glove for handling, and precision assembly works, in dry and/or greasy environment.
- This glove being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.
- This glove shall not be in contact with fire.
- This glove does not contain any recognized carcinogenic or toxic substances, or likely to cause allergies to sensitive persons.
- This glove does not protect against other non-mentioned risks.

SHIPPING AND STORAGE INSTRUCTIONS

- Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C.
- Storage under excessive temperatures and for a long time (>1 month) can lead to the product deterioration.
- By nature, nitrile is sensitive to temperature changes.

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420:2003+A1:2009	Dexterity :	5/5
Mechanical Risks	EN 388:2016	Abrasion resistance: Blade cut resistance: Tear strenght resistance: Puncture resistance: Cut resistance method EN ISO 13997:	4 /4 1 /5 3 /4 1 /4 X /A-F

Creation Date :
01/10/2019-V1

Revision Date :
décembre 2023



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement