



DEXTER CUT

ULTRALIGHT AND COMFORTABLE



©JLFF Pro

R é f : 2304

DESCRIPTION

Glove with nitrile sandy palm coating for handling and assembly works where a cut protection is needed

KEYS FEATURES

- > High cut protection
- > Ultralight : less than 50 g (size 9)
- > 18 gauge : comfortable
- > 2COVER™ process reinforcement

FIELD OF USE

- Handling and/or precision assembly work with cut risks

CHARACTERISTICS

- 18 gauge knitted glove with black nitrile "sandy" palm coating
- 2COVER™ process reinforcement in between the thumb and forefinger to extend lifespan of the product by protecting this critical area
- Silicone free

BENEFITS

- Abrasion and cut resistant
- High precision and dexterity
- Extended lifespan and better comfort

WORKING ENVIRONMENT

- Dry and/or greasy environment



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT

Size

VR / AG : 7 to 11

Standards

- EN 420:2003+A1:2009
- EN 388:2016



DEXTER CUT - REF : 2304

COMPOSITION / MATERIAL

- Knitted gauge 18 with UHMPWE, nylon, fiberglass, Spandex®
- Palm and fingertips black nitrile sandy coating
- Knit wrist 18 gauge with UHMPWE, Nylon, fiberglass, Spandex® and elastic yarn
- Binding color per size

LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

REGULATION

CE marking according to EU 2016/425
Certificate N°0075/2697/162/11/18/2567



USE / CARE INSTRUCTIONS & ADVICES

- Protective glove for light handling in every environment, and precision assembly work where a cut protection is needed.
- This glove being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.
- This glove shall not be in contact with fire.
- This glove does not contain any recognized carcinogenic or toxic substances, or likely to cause allergies to sensitive persons.

SHIPPING AND STORAGE INSTRUCTIONS

- Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C.
- Storage under excessive temperatures and for a long time (>1 month) can lead to the product deterioration.
- By nature, nitrile is sensitive to temperature changes.

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420:2003+A1:2009	Dexterity :	5/5
Mechanical Risks	EN 388:2016	Abrasion resistance: Blade cut resistance: Tear strenght resistance: Puncture resistance: Cut resistance method EN ISO 13997:	4 /4 X /5 4 /4 2 /4 C /A-F

Creation Date :
01/10/2019-V1

Revision Date :
juin 2023



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document