

**INFORMATION & USING INSTRUCTION** 

# **DEXTER CUT**

DESCRIPTION: 18 gauge glove with resistant cut yarn, black nitrile sandy palm coating. Double black nitrile coating between thumb and forefinger. Elasticated knit wrist for a better fit. Silicone free

FIELD OF USE: Protective glove for light handling in any environment even greasy, for fine assembly where a cut protection is necessary.

SIZES :	6	7 🖂	8 🖂	9 🖂	10 🖂	11 🖂	12	13 🗌
---------	---	-----	-----	-----	------	------	----	------

# MARKING



This item complies to the Regulation 2016/425 requirements. It has been subjected to the EC type certificate n° 0075/2697/162/11/18/2567 issued by CTC - (n° 0075) - 4, rue Hermann Frenkel – 69367 Lyon Cedex 07 - FRANCE

#### **STANDARDS REFERENCES**

Properties according to the European standards EN 420+A1 (2009), EN 388 (2016) Un niveau élevé indique une bonne protection. (0 = niveau 1 non atteint ; X = essai non effectué).

## EN 388 (2016) : Mechanical Risks

Г	-	
L	님	
١	<u> </u>	

Abrasion	: <b>4</b> / 4	
<b>Cut</b> couptest	<b>: X</b> / 5	$\sim$
Tear	<b>:4</b> /4	- L li
Puncture	: <b>2</b> / 4	
Cut ISO	: <b>C</b>	

EN 420+A1 (2009) : General requirements Dexterity: 5 / 5

Levels of performances are obtained with tests executed in environment conditions defined in the standards. Thus, each use in new conditions are the concern of user's responsibility.

LIMIT OF USE: Protective glove for light handling in dry or greasy environment, for fine assembly where a cut protection is necessary.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. These gloves have got a tensile strength and must not be used when there is a risk of snapping up by machines in movement. This glove shall not be in contact with fire.

## **CATEGORY PPE II**

STORAGE & MAINTENANCE INSTRUCTIONS: Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C Storage under excessive temperatures and for a long time ( > 1 month) can lead to the product deterioration. By nature, nitrile is sensitive to temperature changes.

Recycling under users responsibility. We do not guarantee the recycled products levels of performance

EC DECLARATION OF CONFORMITY is available on the following website: www.jlf-pro.com

HANDEX 4, Rue du Président Carnot – 69002 LYON FRANCE Tel. : (33) 478370707