



## GRIP 5

### EXCEPTIONAL GRIP



©JLFF Pro



4 X 4 3 C



*R é f : 2306*

#### DESCRIPTION

15 gauge knitted glove with nitrile coating, for assembly works where a cut resistance is required

#### KEYS FEATURES

- > Exceptional grip
- > 2COVER™ process reinforcement

#### FIELD OF USE

- Handling and/or assembly work where a cut protection is needed

#### CHARACTERISTICS

- 15 gauge knitted glove with nitrile foam palm coating
- Reinforcement for a better protection and extended lifespan
- Knitwrist to complete the perfect fit
- Silicone free

#### BENEFITS

- Exceptional grip, perfect for precision assembly works
- Good resistance
- Perfect fit at the wrist

**Size**  
VR : 7 to 11

**Standards**  
· EN 420:2003+A1:2009  
· EN 388:2016

#### WORKING ENVIRONMENT

- Dry and/or greasy environment



#### COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT



GRUPE JLFF - 4 rue du Président Carnot - 69002 Lyon - France  
Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89

**DOWNLOADING**  
OF PRODUCT DATASHEETS AND  
DOCUMENTS ON WEBSITE  
[www.jlff-pro.com](http://www.jlff-pro.com)



GRIP 5 - REF : 2306

## COMPOSITION / MATERIAL

- 15 gauge knitted glove with UHMPWE, nylon, fiberglass, Spandex®
- Palm and fingertips black nitrile coating
- Reinforcement between thumb and forefinger with black nitrile coating
- 15 gauge knit wrist with UHMPWE, nylon, fiberglass, Spandex® and elastic yarn
- Binding color per size

## LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

## REGULATION

CE marking according to EU 2016/425  
Certificate N°0075/2697/162/09/18/1878



## USE / CARE

### INSTRUCTIONS & ADVICES

- Protective glove for handling in dry and wet environment, where a cut protection is needed
- This glove being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.

## SHIPPING AND STORAGE INSTRUCTIONS

- Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C.
- Storage under excessive temperatures and for a long time (>1 month) can lead to the product deterioration.
- By nature, nitrile is sensitive to temperature changes.

## LAB TESTS RESULTS

| STANDARD             | NORMATIVE REFERENCE | TESTING                                                                                                                                   | RESULTS                                     |
|----------------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| General requirements | EN 420:2003+A1:2009 | Dexterity :                                                                                                                               | 5/5                                         |
| Mechanical Risks     | EN 388:2016         | Abrasion resistance:<br>Blade cut resistance:<br>Tear strenght resistance:<br>Puncture resistance:<br>Cut resistance method EN ISO 13997: | 4 / 4<br>X / 5<br>4 / 4<br>3 / 4<br>C / A-F |

Creation Date :  
01/10/2019-V1

Revision Date :  
juin 2023



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89  
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document