



## CRINK

### EXCELLENT GRIP



©JLFF Pro

**R é f : 2307**

#### DESCRIPTION

Knitted glove with 3/4 crinkle coating and double coating at the top of the fingers for handling works

#### KEYS FEATURES

- > Excellent grip
- > Resistant glove
- > High dexterity
- > Long wear

#### FIELD OF USE

- General handling

#### WORKING ENVIRONMENT

- Dry and/or wet environment

#### CHARACTERISTICS

- 13 gauge knitted glove with 3/4 black crinkle latex coating which provides an excellent grip in dry condition and good in wet
- Double blue crinkle latex coating at the top of the fingers to extend the wear
- Knitwrist for a better fit
- Silicone free

#### BENEFITS

- Good grip in wet environment, excellent in dry
- Long wear and resistant
- Perfect fit at the wrist

#### Size

VR / AG : 8 to 11

#### Standards

- EN 420:2003+A1:2009
- EN 388:2016



#### COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT



CRINK - REF : 2307

### COMPOSITION / MATERIAL

- 13 gauge knitted glove with red polyester
- 3/4 black crinkle latex coating
- Second coating on fingertips with blue crinkle latex coating
- 13 gauge knit wrist with red polyester and elastic yarn
- Binding color per size

### LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

### REGULATION

CE marking according to Directive 89/696/CEE

CE type examination certificate : 0075/2697/162/11/17/1675



### USE / CARE INSTRUCTIONS & ADVICES

- Protective glove for handling in dry and wet environment.
- This gloves being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.
- This glove shall not be in contact with fire.

### SHIPPING AND STORAGE INSTRUCTIONS

- Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C.
- Storage under excessive temperatures and for a long time can lead to the product deterioration.

### LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420:2003+A1:2009	Dexterity :	5/5
Mechanical Risks	EN 388:2016	Abrasion resistance: Blade cut resistance: Tear strenght resistance: Puncture resistance: Cut resistance method EN ISO 13997:	2 /4 1 /5 3 /4 1 /4 X /A-F

Creation Date :  
01/10/2019-V1

Revision Date :  
décembre 2020



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89  
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document