

INFORMATIONS & USING INSTRUCTION

CRINK

DESCRIPTION : Knitted coated glove, 13 gauge red polyester glove, 3/4 black crinkle latex coating, top fingers blue double crinkle coating, knit wrist.





This item complies the directive CEE / 89 / 686: innocuity, comfort, strength and to the paragraphs 3.3 & 3.6 of its appendix 2: protection against physical aggressions. It has been subjected to the CE type certificate n° **0075/2697/162/11/17/1675** issued by CTC - (n° 0075) – 4, Rue Hermann Frenkel – 69367 – LYON - Cedex 07 - FRANCE

VALIDATED PERFORMANCES WITH THE FOLLOWING STANDARDS REFERENCES :

According to the European standards EN 420+A1 (2009), EN 388 (2016) A high level shows a good protection. (0 = level 1 not reached ; X = not tested).

EN 388 (2016) : Mechanical Risks

	Abrasion	: 2 / 4
	Cut couptest	:1 /5
	Tear	:3 /4
	Puncture	:1/4
\sim	Cut TDM EN ISO 13997	: X
EN 420+A1 (2009) : General requirements		

Dexterity: 5 / 5

Levels of performance are for the palm only.

Levels of performances are obtained with tests executed in environment conditions definited in the standards. Thus, each use in new conditions are the concern of users responsability.

USING INSTRUCTIONS : Protective glove for handling objects in dry, wet and/or greasy environment.

These gloves have got a tensile strength and must not be used when there is a risk of snapping up by machines in movement. These gloves must not be in contact with fire.

CATEGORY PPE II

STORAGE & MAINTENANCE INSTRUCTIONS : Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C. Storage under excessive temperatures and for a long time (> 1 month) can lead to the product deterioration.

Recycling under users responsability. We do not guarantee the recycled products levels of performance.

HANDEX 4, Rue du Président Carnot – 69002 LYON FRANCE Tel. : (33) 478370707