



CRINK 5

EXCELLENT GRIP



EN 388



3 X 4 4 D

©JLFF Pro

Ref: 2310

DESCRIPTION

13 gauge knitted glove made of cut resistance fiber with 3/4 latex crinkle coating for handling or assembly works where a cut protection is needed.

KEYS FEATURES

- > "Crinkle" coating for good grip
- > High cut resistance
- > Perfect fit

FIELD OF USE

- Handling and/or assembly works where a cut protection is needed

WORKING ENVIRONMENT

- Dry or slightly greasy or wet environments

CHARACTERISTICS

- 13 gauge liner made of cut resistant fibers
- Blue crinkle latex coating palm at the top of the fingers to have a very good grip in dry and good grip in wet environment
- Knitwrist for a perfect fit
- Silicone free

BENEFITS

- Good cut resistance
- Good grip in wet environment, excellent in dry
- Long wear and resistant
- Perfect fit at the wrist

Size

VR : 8 to 11

Standards

- EN 420:2003+A1:2009
- EN 388:2016+A1:2018



COMPLEMENTARY PRODUCTS



0369-WORKER



0610-DESINFECTANT DESODORISANT

DOWNLOADING

OF PRODUCT DATASHEETS AND
DOCUMENTS ON WEBSITE

www.jlff-pro.com



CRINK 5 - REF : 2310

COMPOSITION / MATERIAL

- 13 gauge knitted glove with UHMPWE, nylon, fiberglass
- 3/4 blue crinkle latex coating
- 13 gauge knit wrist with UHMPWE, nylon, fiberglass and elastic yarn
- Binding color per size

LIFESPAN

Recycling under users responsibility. We do not guarantee the recycled products levels of performance.

REGLEMENTARY

CE marking according to EU 2016/425
Certificate N°0075/2697/162/02/20/0491



USE / CARE INSTRUCTIONS & ADVICES

- Protective glove for handling in every environment even greasy, and assembly work where a cut protection is needed.
- This glove being tensile resistant, they must not be used when there is a risk of snapping up by machines in movement.
- This glove shall not be in contact with fire and should not be used to handle objects with temperatures above 50 °C.
- The glove does not protect from liquids and should not be used to handle chemicals or phytosanitary products.
- This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.
- Natural rubber proteins are sensitizers, only a very small number of users may be sensitized to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.
- This glove does not protect the risks not mentioned in this document.

SHIPPING AND STORAGE INSTRUCTIONS

- Keep in the original packaging, normal temperature and moisture, opened and ventilated room.
- Observe the rules of hygiene and after each use check that PPE does not have any tear, hole, or dirt on the glove which could lead to less protection and properties of the item. If damaged the glove must be thrown on scrapheap.
- The design performance can not be significantly affected by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

LAB TESTS RESULTS

STANDARD	NORMATIVE REFERENCE	TESTING	RESULTS
General requirements	EN 420:2003+A1:2009	Dexterity :	5/5
Mechanical Risks	EN 388:2016+A1:2018	Abrasion resistance: Blade cut resistance: Tear strength resistance: Puncture resistance: Cut resistance method EN ISO 13997:	3 / 4 X / 5 4 / 4 4 / 4 D / A-F

Creation Date :
10-2020-V1

Revision Date :
décembre 2024



Label awarded according to specifications derived from the ISO 26 000 standard and audited annually by Ecocert Environnement



GROUPE JLF - 4 rue du Président Carnot - 69002 Lyon – France - Tél. +33 (0)4 78 37 07 37 – Fax. +33 (0)4 78 37 62 89
SAS CAPITAL 361 760 € - RCS ANGOULEME B 314284134 - CODE APE 1520Z - CODE TVA FR 95 314 284 134 - N°SIRET 314 284 134 00041

GROUPE JLF reserves the right to modify the manufacturing characteristics of the product. Non contractual document