



INFORMATION & USING INSTRUCTIONS

SIGMA 3

DESCRIPTION: 13 gauge glove with cut resistant yarn, grey polyurethane palm coating. Elasticated knit wrist for a better fit. Silicone free

FIELD OF USE: Protective glove for light handling or for fine assembly in any environment even slightly greasy, where a cut protection is necessary.

SIZES: 6 ☒ 7 ☒ 8 ☒ 9 ☒ 10 ☒ 11 ☒ 12 ☐ 13 ☐

MARKING



This item complies to the Regulation 2016/425 requirements.

It has been subjected to the EC type certificate n° 0075/2697/162/11/18/2685 issued by CTC - (n° 0075) – 4, rue Hermann Frenkel – 69367 Lyon Cedex 07 - FRANCE

STANDARDS REFERENCES

Properties according to the European standards EN 420+A1 (2009), EN 388 (2016)

A high level shows a good protection. (0 = level 1 not reached; X = not tested).

EN 388 (2016) : Mechanical Risks



Abrasion	: 4 / 4
Cut <i>coupé</i>	: X / 5
Tear	: 4 / 4
Puncture	: 3 / 4
Cut ISO	: B



EN 420+A1 (2009) : General requirements

Dexterity : 5 / 5

Levels of performances are obtained with tests executed in environment conditions defined in the standards.
Thus, each use in new conditions are the concern of user's responsibility.

LIMIT OF USE: Protective glove for light handling or fine assembly in dry or slightly greasy environment, where a cut protection is necessary.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

These gloves have got a tensile strength and must not be used when there is a risk of snapping up by machines in movement.

This glove must not be in contact with fire.

CATEGORY PPE II

STORAGE & MAINTENANCE INSTRUCTIONS: Keep sheltered from light and humidity, preferably in ventilated rooms with a temperature between 5°C to 25°C Storage under excessive temperatures and for a long time (> 1 month) can lead to the product deterioration.

Recycling under user's responsibility. We do not guarantee the recycled products levels of performance

EC DECLARATION OF CONFORMITY is available on the following website: www.jlf-pro.com